Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Belgium

SAFETY DATA SHEET

Q8 Handel 68



SECTION 1: Identific	cation of the substance/mixture and of the company/
undertaking	
1.1 Product identifier	
Product name	: Q8 Handel 68
Viscosity or Type	: ISO VG 68
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Material uses	: Lubricating oil for hydraulic equipment
1.3 Details of the supplier of	f the safety data sheet
Supplier	: Kuwait Petroleum Companies in the Benelux Company Office: Brusselstraat 59, 2018 Antwerp, Belgium Contactaddress: Petroleumkaai 7, 2020 Antwerp, Belgium Tel. +32 3 247 38 11, Fax +32 3 216 03 42
Manufacturer / Distributor	 Kuwait Petroleum Belgium N.V./S.A. Petroleumkaai 7 B-2020 Antwerp Belgium Italy Q8Oils Italia S.r.I. Via Volpedo 2 15050 Castellar Guidobono (AL) Italy
e-mail address of person responsible for this SDS	: SDSinfo@Q8.com, communication preferably in English only.
PCN Information contact	: PCNinfo@Q8.com, communication preferably in English only.
1.4 Emergency telephone nu	umber
Europe	: +44 (0) 1235 239 670 CARECHEM24
Global (English only)	: +44 (0) 1865 407 333
National advisory body/Po	ison Center
Belgium	: Poison Centre : +32 (0)70 245 245
SECTION 2: Hazards	s identification
2.1 Classification of the sub	stance or mixture
Product definition	: Mixture
Classification according to	Regulation (EC) No. 1272/2008 [CLP/GHS]
Not classified.	
The product is not classified	as hazardous according to Regulation (EC) 1272/2008 as amended.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown: None.toxicityIngredients of unknown: None.

ecotoxicity

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
Prevention	: Not applicable.

Date of issue/Date of revision

: 28-11-2022 Date of previous issue

sue : 20-07-2020

SECTION 2: Hazards identification

Response	1	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains methyl methacrylate. May produce an allergic reaction. Safety data sheet available on request.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Detergents - Regulation (EC) No 648/2004	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	1	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.
fastenings Tactile warning of danger 2.3 Other hazards Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Severely refined mineral oil (C15 - C50) - Not classified.	CAS: *	≥75 - ≤90	Not classified.	-	[2]
Severely refined mineral oil (C15 - C50) - H304	CAS: *	≥10 - ≤25	Asp. Tox. 1, H304	-	[1] [2]
methyl methacrylate	REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6	≤0.3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

Contains one or more of the following:

CAS: 64741-88-4, EC: 265-090-8, EU REACH: 01-2119488706-23

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25

CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29

CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Belgium

Q8 Handel 68

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid n	neasures
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse. High pressure skin injections are serious medical emergencies. Injury will not appear serious at first. Within a few hours, tissue will become swollen, discolored and extremely painful.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact Inhalation	No specific data.No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	;
Creatific treatments	No oppositio tractment	

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

•		
5.1 Extinguishing media		
Suitable extinguishing media	:	Use dry chemical, CO ₂ , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	:	Do not use water jet.
5.2 Special hazards arising f	ron	ו the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	 See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations

- : Not available. : Not available.
- Industrial sector specific solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Severely refined mineral oil (C15 - C50) - Not classified.	Limit values (Belgium, 5/2021). [] TWA: 5 mg/m ³ 8 hours. Form: mist STEL: 10 mg/m ³ 15 minutes. Form: mist EU OEL (Europe). TWA: 5 mg/m ³ 8 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Severely refined mineral oil (C15 - C50) - H304	Limit values (Belgium, 5/2021). [] TWA: 5 mg/m ³ 8 hours. Form: mist STEL: 10 mg/m ³ 15 minutes. Form: mist EU OEL (Europe). TWA: 5 mg/m ³ 8 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
methyl methacrylate	Limit values (Belgium, 5/2021). TWA: 50 ppm 8 hours. TWA: 208 mg/m ³ 8 hours. STEL: 416 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. EU OEL (Europe, 10/2019). Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.

SECTION 8: Exposure controls/personal protection

Recommended monitoring : procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
--	--

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
methyl methacrylate	DNEL	Long term Dermal	8.2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	13.67 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	74.3 mg/m ³	General population	Systemic
	DNEL	Long term	104 mg/m³	General population	Local
	DNEL	Long term Inhalation	208 mg/m³	Workers	Local
	DNEL	Long term Inhalation	208 mg/m³	Workers	Systemic
	DNEL	Short term Dermal	1.5 mg/cm ²	General population	Local
	DNEL	Long term Dermal	1.5 mg/cm ²		Local
	DNEL	Short term Dermal	1.5 mg/cm ²		Local
	DNEL	Long term Dermal	1.5 mg/cm ²		Local
	DNEL	Long term Oral	8.2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	208 mg/m ³	General population	Local
	DNEL	Short term Inhalation	416 mg/m³	Workers	Local

PNECs

No PNECs available.

8.2 Exposure controls Appropriate engineering controls	:	contaminan	ral ventilation shou Its.	ıld be sufficien	t to control we	orker exposur	e to airb	orne
Individual protection meas	ures							
Hygiene measures	:	before eatir Appropriate Wash conta	ls, forearms and fa ng, smoking and u e techniques shoul aminated clothing vers are close to th	sing the lavato d be used to re before reusing	ry and at the emove potenti . Ensure that	end of the wo	rking per ated clot	thing.
Eye/face protection	:	assessmen gases or du	vear complying wit it indicates this is r ists. If contact is p assessment indica s.	necessary to av possible, the fo	void exposure	e to liquid spla ction should b	shes, m e worn,	ists,
Skin protection								
Date of issue/Date of revision		: 28-11-2022	Date of previous is:	sue : 20-0)7-2020	Version	: 1.06	6/16

SECTION 8: Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should
	be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties **Appearance Physical state** : Liquid. [Oily liquid.] Appearance : Clear. Color : Yellow [Light] Odor : Characteristic. : Not available. **Odor threshold** Melting point/freezing point : Not applicable. **Pour point** : ✓-30°C (<-22°F) [ASTM D 97]</p> Initial boiling point and : >300°C (>572°F) boiling range Flammability : Not applicable. Lower and upper explosion : Not available. limit **Flash point** : Open cup: >196°C (>384.8°F) [ASTM D92.] : >300°C (>572°F) **Auto-ignition temperature** : >300°C **Decomposition temperature** Not applicable. pH 2 Kinematic (40°C (104°F)): 68 mm²/s (68 cSt) [ASTM D 445] Viscosity 2 Kinematic (100°C (212°F)): 11.6 mm²/s (11.6 cSt) [ASTM D 445] Solubility(ies) ŝ

Media Result Øold water hot water Not soluble Not soluble Partition coefficient: n-octanol/ water Not applicable. Vapor pressure Density : Ø0.01 kPa (<0.075006 mm Hg)</td> : Ø.88 g/cm³ [15°C (59°F)] [ASTM D 4052]

Date of issue/Date of revision

SECTION 9: Physical and chemical properties

Vapor density	: Not available.
Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: Strong oxidizing materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil	LC50 Inhalation Dusts and	Rat - Male,	5.53 mg/l	4 hours
(C15 - C50) - Not classified.	mists	Female	_	
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Severely refined mineral oil	LC50 Inhalation Dusts and	Rat - Male,	5.53 mg/l	4 hours
(C15 - C50) - H304	mists	Female		
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
methyl methacrylate	LC50 Inhalation Vapor	Rat	78000 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	7872 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Severely refined mineral oil (C15 - C50) - Not classified.	N/A	N/A	N/A	N/A	5.53
Severely refined mineral oil (C15 - C50) - H304 methyl methacrylate	N/A 7872	N/A N/A	N/A N/A	N/A 78	5.53 N/A

Irritation/Corrosion

SECTION 11: Toxicological information

		-		-	-
Product/ingredient name	Result	Species	Score	Exposure	Observation
Severely refined mineral oil (C15 - C50) - Not classified.	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema	Rabbit	0	72 hours	7 days
	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
Severely refined mineral oil (C15 - C50) - H304	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema Skin - Erythema/Eschar	Rabbit Rabbit	0 0.17	72 hours 72 hours	7 days 7 days

Conclusion/Summary :

: Not available.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Severely refined mineral oil (C15 - C50) - Not classified.	skin	Guinea pig	Not sensitizing
Severely refined mineral oil (C15 - C50) - H304	skin	Guinea pig	Not sensitizing

Conclusion/Summary : Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Severely refined mineral oil (C15 - C50) - Not classified.	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
Severely refined mineral oil (C15 - C50) - H304	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

Conclusion/Summary : Not available.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Negative - Dermal - TC	Mouse - Female	-	78 weeks
Severely refined mineral oil (C15 - C50) - H304	Negative - Dermal - TC	Mouse - Female	-	78 weeks

Conclusion/Summary : Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Negative	Negative	Negative	,	Oral: 1000 mg/ kg	-
Severely refined mineral oil (C15 - C50) - H304	Negative	Negative	Negative	,	Oral: 1000 mg/ kg	-

Conclusion/Summary

: Not available.

Teratogenicity

SECTION 11: Toxicological information

	5			
Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Negative - Dermal	Rat	2000 mg/kg	7 days per week
Severely refined mineral oil (C15 - C50) - H304	Negative - Dermal	Rat	2000 mg/kg	7 days per week

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
methyl methacrylate	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Severely refined mineral oil (C15 - C50) - H304	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Not available.
Potential acute health effects	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	sical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.
Delayed and immediate effect	ts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day
()	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week
	Sub-acute NOAEL Inhalation	Rat - Male	>980 mg/m ³	4 weeks; 5 days per week
Severely refined mineral oil (C15 - C50) - H304	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day
	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m³	4 weeks; 5 days per week
Conclusion/Summary	: Not available.			
General	: Prolonged or repeated conta or dermatitis.	act can defat the	skin and lead to irri	tation, cracking and

Carcinogenicity : No known significant effects or critical hazards.
--

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Severely refined mineral oil (C15 - C50) - Not classified.	Acute NEL >100 mg/l Fresh water	Algae	72 hours
,	Acute NEL >10000 mg/l Fresh water	Daphnia - Daphnia Magma	48 hours
	Acute NEL ≥100 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia magna	21 days
Severely refined mineral oil (C15 - C50) - H304	Acute NEL >100 mg/l Fresh water	Algae	72 hours
,	Acute NEL >10000 mg/l Fresh water	Daphnia - Daphnia Magma	48 hours
	Acute NEL ≥100 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia magna	21 days
methyl methacrylate	Acute LC50 130000 µg/l Fresh water	Fish - Pimephales promelas - Adult	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary	: Not available.
--------------------	------------------

quatic half-life	Photolysis	Biodegradability
		Inherent Inherent
	uatic half-life	-

12.3 Bioaccumulative potential

SECTION 12: Ecological information

 Product/ingredient name	LogPow	BCF	Potential
methyl methacrylate	1.38	-	low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product Methods of disp

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

European waste catalogue (EWC)

Waste code	Waste designation
13 01 10*	mineral based non-chlorinated hydraulic oils
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information ADR/RID ADN IMDG ΙΑΤΑ 14.1 UN number Not regulated. Not regulated. Not regulated. Not regulated. or ID number 14.2 UN proper shipping name 12/16 Date of issue/Date of revision : 28-11-2022 : 20-07-2020 Date of previous issue Version : 1.06

SECTION 14: Transport information					
14.3 Transport hazard class(es)	-	-	-	-	
14.4 Packing group	-	-	-	-	
14.5 Environmental hazards	No.	No.	No.	No.	

user

14.6 Special precautions for : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: Not available. 14.7 Maritime transport in bulk according to IMO

instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Other EU regulations**

Industrial emissions : Not listed (integrated pollution prevention and control) -Air : Not listed Industrial emissions (integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU) Not listed.

Prior Informed Consent (PIC) (649/2012/EU) Not listed.

Persistent Organic Pollutants Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive. **National regulations**

SECTION 15: Regulatory information

Germany Hazard class for water : 1

(WGK) Switzerland

VOC content

: Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol Not listed.

NUL IISLEU.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	1	Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.
New Zealand	1	All components are listed or exempted.
Philippines	:	Not determined.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States of America	:	Al components are active or exempted.
Viet Nam	1	Not determined.
15.2 Chemical Safety		Chemical Safety Assessments for all substances in this product are either Complete

15.2 Chemical Safety Assessment

: Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

14/16

SECTION 16: Other information

Indicates information that has changed from previously issued version. **Abbreviations and** ÷. KDN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway acronyms ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ASTM = American Society for Testing and Materials ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DIN = German Institute for Standardization DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

SECTION 16: Other information

EC = European Commission
EC50 = Half maximal effective concentration
EN = European Standard (Norm)
EUH statement = CLP-specific Hazard statement
GHS - Globally Harmonized System of Classification and Labeling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IC50 = Half maximal inhibitory concentration
IMDG = International Maritime Dangerous Goods
IMO = International Maritime Organisation
ISO = International Organization for Standardization
LC50 = Median lethal concentration
LD50 = Median lethal dose
LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration
MARPOL = International Convention for the Prevention of Pollution From Ships,
1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration
NOEL / NOEC = No Observed Effect Level / Concentration
OECD = Organisation for Economic Co-operation and Development
OEL = Occupational Exposure Limit
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
Regulation [Regulation (EC) No. 1907/2006]
RID = The Regulations concerning the International Carriage of Dangerous Goods
by Rail
SDS = Safety Data Sheet
SVHC = Substances of Very High Concern
STEL = Short Term Exposure Limit
TLV = Threshold Limit Value
TWA = Time Weighted Average
UFI = Unique Formula Identifier
UN = United Nations
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of abbreviated H statements

⊮ 225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Full text of classifications [CLP/GHS]

Flam. Liq. 2 Skin Irrit. 2 Skin Sens. 1	ASPIRATION HAZARD - Category FLAMMABLE LIQUIDS - Category SKIN CORROSION/IRRITATION - SKIN SENSITIZATION - Category SPECIFIC TARGET ORGAN TOXI	2 Category 2 1	Category 3		
Training advice	: Ensure operatives are tra	ained to minimise exposures.			I
Date of printing	: 28-11-2022				
Date of issue/Date of revisio	n : 28-11-2022 Date of previ	ous issue : 20-07-2020	Version	:1.06	15/16

SECTION 16: Other information		
Date of issue/ Date of revision	: 28-11-2022	
Date of previous issue	: 20-07-2020	
Version	: 1.06	
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands	

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.