

# SAFETY DATA SHEET

## Q8 T 3000



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : Q8 T 3000  
**UFI** : 0600-40WR-Q007-5KQG

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Lubricating oil for tractors

#### 1.3 Details of the supplier of the safety data sheet

**Supplier** : Q8 Danmark A/S  
Arne Jacobsens Allé 7  
2300 København S, Danmark  
Tel.: +45 7012 4545  
Email: produktteknik@Q8.dk  
Web: www.Q8.dk

**Manufacturer / Distributor** : Kuwait Petroleum Belgium N.V./S.A. / Q8Oils Italia S.r.l.  
Petroleumkaai 7  
B-2020 Antwerp  
Belgium  
Via Volpedo 2  
15050 Castellar Guidobono (AL)  
Italy

**e-mail address of person responsible for this SDS** : SDSinfo@Q8.com, communication preferably in English only.

**PCN Information contact** : PCNinfo@Q8.com, communication preferably in English only.

#### 1.4 Emergency telephone number

**Denmark** : +45 8988 2286  
**Europe** : +44 (0) 1235 239 670  
**Global (English only)** : +44 (0) 1865 407 333



#### National advisory body/Poison Center

**Denmark** : Bispebjerg Hospital - poison line : +45 8212 1212

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

**SERIOUS EYE DAMAGE/ EYE IRRITATION** Category 2 H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

**Ingredients of unknown toxicity** : None.

**Ingredients of unknown ecotoxicity** : None.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Q8 T 3000

## SECTION 2: Hazards identification

**Hazard pictograms** :



**Signal word** :

Warning

**Hazard statements** :

H319 - Causes serious eye irritation.

**Precautionary statements**

**Prevention** :

P280 - Wear eye or face protection.

**Response** :

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.

**Storage** :

Not applicable.

**Disposal** :

Not applicable.

**Supplemental label elements** :

Contains Benzenesulfonic acid, propenated, calcium salt, overbased and 2-tetradecyloxirane, reaction products with boric acid. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

Not applicable.

**Detergents - Regulation (EC) No 648/2004** :

Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** :

Not applicable.

**Tactile warning of danger** :

Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** :

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** :

Prolonged or repeated contact may dry skin and cause irritation.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** :

Mixture

| Product/ingredient name                                    | Identifiers   | %    | Classification                                 | Specific Conc. Limits, M-factors and ATEs | Type |
|--|---|------|--|---|------|
| Severely refined mineral oil (C15 - C50) - Not classified. | CAS: *  | ≥90  | Not classified.                                | -   | [2]  |
| zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)       | REACH #: 01-2119493635-27<br>EC: 224-235-5<br>CAS: 4259-15-8  | <2.5 | Eye Dam. 1, H318<br>Aquatic Chronic 2, H411    | -   | [1]  |
| Benzenesulfonic acid, propenated, calcium salt, overbased  | REACH #: 01-2119657986-16<br>EC: 701-205-4<br>CAS: 68610-84-4 | <1   | Skin Sens. 1B, H317<br>Aquatic Chronic 4, H413 | Skin Sens. 1, H317: C ≥ 2%                | [1]  |

**Date of issue/Date of revision** :

14-10-2022

**Date of previous issue** :

29-12-2020

**Version** : 1.01

2/16

Q8 T 3000

### SECTION 3: Composition/information on ingredients

|  |   |      |  |   |         |
|--|---|------|--|---|---------|
| 2-tetradecyloxirane, reaction products with boric acid | REACH #:<br>01-2119976364-28<br>EC: 701-392-2 | <1   | Skin Sens. 1B, H317  | - | [1]     |
| Severely refined mineral oil (C15 - C50) - H304        | CAS: *  | ≤0.3 | Asp. Tox. 1, H304<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | - | [1] [2] |

Contains one or more of the following:

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25

CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29

CAS: 64742-56-9, EC: 265-159-2, EU REACH: 01-2119480132-48

CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Over-exposure signs/symptoms

Q8 T 3000

## SECTION 4: First aid measures

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, alcohol-resistant foam or water spray (fog).
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
sulfur oxides  
phosphorus oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Q8 T 3000

## SECTION 6: Accidental release measures

**6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Q8 T 3000

## SECTION 8: Exposure controls/personal protection

| Product/ingredient name                                    | Exposure limit values   |
|--|---|
| Severely refined mineral oil (C15 - C50) - Not classified. | <b>Working Environment Authority (Denmark, 6/2021).</b> ☐<br>TWA: 1 mg/m <sup>3</sup> 8 hours. Form: mist and particles<br><b>EU OEL (Europe).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Mist<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist |
| Severely refined mineral oil (C15 - C50) - H304            | <b>Working Environment Authority (Denmark, 6/2021).</b> ☐<br>TWA: 1 mg/m <sup>3</sup> 8 hours. Form: mist and particles<br><b>EU OEL (Europe).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Mist<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

| Product/ingredient name                               | Type  | Exposure              | Value                  | Population              | Effects            |          |
|---|---|-----------------------|------------------------|-------------------------|--------------------|----------|
| Zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate) | DNEL  | Long term Oral        | 0.19 mg/kg bw/day      | General population      | Systemic           |          |
|   | DNEL  | Long term Inhalation  | 1.67 mg/m <sup>3</sup> | General population      | Systemic           |          |
|   | DNEL  | Long term Dermal      | 4.8 mg/kg bw/day       | General population      | Systemic           |          |
|   | DNEL  | Long term Inhalation  | 6.6 mg/m <sup>3</sup>  | Workers                 | Systemic           |          |
|   | DNEL  | Long term Dermal      | 9.6 mg/kg bw/day       | Workers                 | Systemic           |          |
|   | Benzenesulfonic acid, propenated, calcium salt, overbased | DNEL                  | Long term Oral         | 1.7 mg/kg bw/day        | General population | Systemic |
|   |   | DNEL                  | Long term Dermal       | 4.17 mg/kg bw/day       | General population | Systemic |
|   |   | DNEL                  | Long term Dermal       | 8.33 mg/kg bw/day       | Workers            | Systemic |
|   |   | DNEL                  | Long term Inhalation   | 11.8 mg/m <sup>3</sup>  | General population | Systemic |
|   |   | DNEL                  | Long term Inhalation   | 25.55 mg/m <sup>3</sup> | Workers            | Systemic |
|   |   | DNEL                  | Short term Dermal      | 50 mg/kg bw/day         | General population | Systemic |
|   |   | DNEL                  | Short term Dermal      | 100 mg/kg bw/day        | Workers            | Systemic |
|   |   | DNEL                  | Short term Inhalation  | 267.2 mg/m <sup>3</sup> | General population | Systemic |
|   | DNEL  | Short term Inhalation | 668 mg/m <sup>3</sup>  | Workers                 | Systemic           |          |

### PNECs

No PNECs available.

## 8.2 Exposure controls

## SECTION 8: Exposure controls/personal protection

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** :  Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid. [Oily liquid.]
- Appearance** : Clear.
- Color** : Brown. [Light]
- Odor** : Slight
- Odor threshold** : Not available.
- Melting point/freezing point** : Not applicable.
- Pour point** :  -27°C (<-16.6°F) [ASTM D 97]
- Initial boiling point and boiling range** : >300°C (>572°F)
- Flammability** : Not applicable.

Q8 T 3000

## SECTION 9: Physical and chemical properties

|  |   |
|--|---|
| <b>Lower and upper explosion limit</b> | : Not available.  |
| <b>Flash point</b>                     | : Open cup: >220°C (>428°F) [ASTM D92.]   |
| <b>Auto-ignition temperature</b>       | : >300°C (>572°F)   |
| <b>Decomposition temperature</b>       | : >300°C  |
| <b>pH</b>                              | : <input checked="" type="checkbox"/> Not applicable.   |
| <b>Viscosity</b>                       | : <input checked="" type="checkbox"/> Kinematic (40°C (104°F)): 84.8 mm <sup>2</sup> /s (84.8 cSt) [ASTM D 445]<br>Kinematic (100°C (212°F)): 10.6 mm <sup>2</sup> /s (10.6 cSt) [ASTM D 445] |
| <b>Solubility(ies)</b>                 | :   |

| Media   | Result                     |
|---|----------------------------|
| <input checked="" type="checkbox"/> Cold water<br>hot water | Not soluble<br>Not soluble |

|  |  |
|--|--|
| <b>Partition coefficient: n-octanol/ water</b> | : <input checked="" type="checkbox"/> Not applicable.                                    |
| <b>Vapor pressure</b>                          | : <input checked="" type="checkbox"/> 0.01 kPa (<0.075006 mm Hg)                         |
| <b>Density</b>                                 | : <input checked="" type="checkbox"/> 0.88 g/cm <sup>3</sup> [15°C (59°F)] [ASTM D 4052] |
| <b>Vapor density</b>                           | : Not available.   |
| <b>Explosive properties</b>                    | : Not applicable.  |
| <b>Oxidizing properties</b>                    | : Not applicable.  |
| <b>Particle characteristics</b>                |  |
| <b>Median particle size</b>                    | : <input checked="" type="checkbox"/> Not applicable.                                    |

## SECTION 10: Stability and reactivity

|  |  |
|--|--|
| <b>10.1 Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.           |
| <b>10.2 Chemical stability</b>                 | : The product is stable.   |
| <b>10.3 Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| <b>10.4 Conditions to avoid</b>                | : No specific data.  |
| <b>10.5 Incompatible materials</b>             | : Reactive or incompatible with the following materials:<br>Strong oxidizing materials                 |
| <b>10.6 Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## SECTION 11: Toxicological information

|  |
|--|
| <b>11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008</b> |
| <b>Acute toxicity</b>  |



Q8 T 3000

## SECTION 11: Toxicological information

| Product/ingredient name  | Result                          | Species            | Dose        | Exposure |
|--|---------------------------------|--------------------|-------------|----------|
| Severely refined mineral oil (C15 - C50) - Not classified.<br><br>zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) | LC50 Inhalation Dusts and mists | Rat - Male, Female | 5.53 mg/l   | 4 hours  |
|  | LD50 Dermal                     | Rabbit             | >5000 mg/kg | -        |
|  | LD50 Oral                       | Rat                | >5000 mg/kg | -        |
|  | LD50 Dermal                     | Rabbit             | >5 g/kg     | -        |
| Severely refined mineral oil (C15 - C50) - H304  | LD50 Oral                       | Rat                | 3.1 g/kg    | -        |
|  | LC50 Inhalation Dusts and mists | Rat - Male, Female | 5.53 mg/l   | 4 hours  |
|  | LD50 Dermal                     | Rabbit             | >5000 mg/kg | -        |
|  | LD50 Oral                       | Rat                | >5000 mg/kg | -        |

**Conclusion/Summary** : Not available.

### Acute toxicity estimates

| Product/ingredient name                                    | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| Severely refined mineral oil (C15 - C50) - Not classified. | N/A          | N/A            | N/A                      | N/A                        | 5.53                                |
| zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)       | 3100         | N/A            | N/A                      | N/A                        | N/A                                 |
| Severely refined mineral oil (C15 - C50) - H304            | N/A          | N/A            | N/A                      | N/A                        | 5.53                                |

### Irritation/Corrosion

| Product/ingredient name                                    | Result                             | Species | Score | Exposure | Observation |
|--|------------------------------------|---------|-------|----------|-------------|
| Severely refined mineral oil (C15 - C50) - Not classified. | Eyes - Iris lesion                 | Rabbit  | 0     | 48 hours | 72 hours    |
|  | Eyes - Redness of the conjunctivae | Rabbit  | 0.33  | 48 hours | 72 hours    |
| Severely refined mineral oil (C15 - C50) - H304            | Skin - Edema                       | Rabbit  | 0     | 72 hours | 7 days      |
|  | Skin - Erythema/Eschar             | Rabbit  | 0.17  | 72 hours | 7 days      |
|  | Eyes - Iris lesion                 | Rabbit  | 0     | 48 hours | 72 hours    |
|  | Eyes - Redness of the conjunctivae | Rabbit  | 0.33  | 48 hours | 72 hours    |
|  | Skin - Edema                       | Rabbit  | 0     | 72 hours | 7 days      |
|  | Skin - Erythema/Eschar             | Rabbit  | 0.17  | 72 hours | 7 days      |

**Conclusion/Summary** : Not available.

### Sensitization

| Product/ingredient name                                    | Route of exposure | Species    | Result          |
|--|-------------------|------------|-----------------|
| Severely refined mineral oil (C15 - C50) - Not classified. | skin              | Guinea pig | Not sensitizing |
| Severely refined mineral oil (C15 - C50) - H304            | skin              | Guinea pig | Not sensitizing |

**Conclusion/Summary** : Not available.

### Mutagenicity

| Product/ingredient name                                    | Test  | Experiment  | Result   |
|--|---|---|----------|
| Severely refined mineral oil (C15 - C50) - Not classified. | 474 Mammalian Erythrocyte Micronucleus Test | Experiment: In vivo<br>Subject: Mammalian-Animal<br>Cell: Somatic | Negative |
| Severely refined mineral oil (C15 - C50) - H304            | 474 Mammalian Erythrocyte Micronucleus Test | Experiment: In vivo<br>Subject: Mammalian-Animal<br>Cell: Somatic | Negative |

**Conclusion/Summary** : Not available.

Q8 T 3000

## SECTION 11: Toxicological information

### Carcinogenicity

| Product/ingredient name                                    | Result                 | Species        | Dose | Exposure |
|--|------------------------|----------------|------|----------|
| Severely refined mineral oil (C15 - C50) - Not classified. | Negative - Dermal - TC | Mouse - Female | -    | 78 weeks |
| Severely refined mineral oil (C15 - C50) - H304            | Negative - Dermal - TC | Mouse - Female | -    | 78 weeks |

**Conclusion/Summary** : Not available.

### Reproductive toxicity

| Product/ingredient name                                    | Maternal toxicity | Fertility | Development toxin | Species            | Dose                | Exposure |
|--|-------------------|-----------|-------------------|--------------------|---------------------|----------|
| Severely refined mineral oil (C15 - C50) - Not classified. | Negative          | Negative  | Negative          | Rat - Male, Female | Oral:<br>1000 mg/kg | -        |
| Severely refined mineral oil (C15 - C50) - H304            | Negative          | Negative  | Negative          | Rat - Male, Female | Oral:<br>1000 mg/kg | -        |

**Conclusion/Summary** : Not available.

### Teratogenicity

| Product/ingredient name                                    | Result            | Species | Dose       | Exposure        |
|--|-------------------|---------|------------|-----------------|
| Severely refined mineral oil (C15 - C50) - Not classified. | Negative - Dermal | Rat     | 2000 mg/kg | 7 days per week |
| Severely refined mineral oil (C15 - C50) - H304            | Negative - Dermal | Rat     | 2000 mg/kg | 7 days per week |

**Conclusion/Summary** : Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

| Product/ingredient name                         | Result                         |
|---|--------------------------------|
| Severely refined mineral oil (C15 - C50) - H304 | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking

Q8 T 3000

## SECTION 11: Toxicological information

**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

| Product/ingredient name                                    | Result                           | Species            | Dose                   | Exposure                  |
|--|----------------------------------|--------------------|------------------------|---------------------------|
| Severely refined mineral oil (C15 - C50) - Not classified. | Sub-acute LOAEL Oral             | Rat - Male         | 125 mg/kg              | 13 weeks; 5 hours per day |
|  | Sub-chronic NOAEL Oral           | Rat - Male, Female | ≥2000 mg/kg            | 13 weeks; 5 days per week |
| Severely refined mineral oil (C15 - C50) - H304            | Sub-acute NOAEL Inhalation Vapor | Rat - Male         | >980 mg/m <sup>3</sup> | 4 weeks; 5 days per week  |
|  | Sub-acute LOAEL Oral             | Rat - Male         | 125 mg/kg              | 13 weeks; 5 hours per day |
|  | Sub-chronic NOAEL Oral           | Rat - Male, Female | ≥2000 mg/kg            | 13 weeks; 5 days per week |
|  | Sub-acute NOAEL Inhalation Vapor | Rat - Male         | >980 mg/m <sup>3</sup> | 4 weeks; 5 days per week  |

**Conclusion/Summary** : Not available.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name                                    | Result                            | Species                    | Exposure |
|--|-----------------------------------|----------------------------|----------|
| Severely refined mineral oil (C15 - C50) - Not classified. | Acute NEL >100 mg/l Fresh water   | Algae                      | 72 hours |
|  | Acute NEL >10000 mg/l Fresh water | Daphnia - Daphnia Magma    | 48 hours |
|  | Acute NEL ≥100 mg/l Fresh water   | Fish - Pimephales promelas | 96 hours |
|  | Chronic NEL 10 mg/l Fresh water   | Daphnia - Daphnia magna    | 21 days  |
|  | Acute NEL >100 mg/l Fresh water   | Algae                      | 72 hours |
| Severely refined mineral oil (C15 - C50) - H304            | Acute NEL >10000 mg/l Fresh water | Daphnia - Daphnia Magma    | 48 hours |
|  | Acute NEL ≥100 mg/l Fresh water   | Fish - Pimephales promelas | 96 hours |
|  | Chronic NEL 10 mg/l Fresh water   | Daphnia - Daphnia magna    | 21 days  |

**Conclusion/Summary** : Not available.

Q8 T 3000

## SECTION 12: Ecological information

### 12.2 Persistence and degradability

| Product/ingredient name                              | Test | Result        | Dose | Inoculum |
|--|------|---------------|------|----------|
| Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) | -    | 5 % - 27 days | -    | -        |

**Conclusion/Summary** : Not available.

| Product/ingredient name                                    | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| Severely refined mineral oil (C15 - C50) - Not classified. | -                 | -          | Inherent         |
| zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)       | -                 | -          | Not readily      |
| Severely refined mineral oil (C15 - C50) - H304            | -                 | -          | Inherent         |

### 12.3 Bioaccumulative potential

| Product/ingredient name                                   | LogP <sub>ow</sub> | BCF | Potential |
|---|--------------------|-----|-----------|
| Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)      | 3.59               | -   | low       |
| Benzenesulfonic acid, propenated, calcium salt, overbased | -                  | 64  | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### European waste catalogue (EWC)

Q8 T 3000

## SECTION 13: Disposal considerations

| Waste code | Waste designation   |
|------------|---|
| 13 02 05*  | mineral-based non-chlorinated engine, gear and lubricating oils |

### Packaging

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|  | ADR/RID        | ADN            | IMDG           | IATA           |
|--|----------------|----------------|----------------|----------------|
| <b>14.1 UN number or ID number</b>     | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| <b>14.2 UN proper shipping name</b>    | -              | -              | -              | -              |
| <b>14.3 Transport hazard class(es)</b> | -              | -              | -              | -              |
| <b>14.4 Packing group</b>              | -              | -              | -              | -              |
| <b>14.5 Environmental hazards</b>      | No.            | No.            | No.            | No.            |

- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

- 14.7 Maritime transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorization

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

Q8 T 3000

## SECTION 15: Regulatory information

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

### Ozone depleting substances (1005/2009/EU)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product is not controlled under the Seveso Directive.

### National regulations

**Product registration number** : PR-nr: 1698800

**MAL-code** : 00-1

**Protection based on MAL** : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 00-1

**Application:** When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During all spraying where atomization occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Full mask with combined filter, coveralls and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

Q8 T 3000

## SECTION 15: Regulatory information

\*See Regulations.

**Hazard class for water (WGK)** : 

**VOC content** : Exempt.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

**Australia** : Not determined.

**Canada** : Not determined.

**China** : Not determined.

**Eurasian Economic Union** :  **Russian Federation inventory**: Not determined.

**Japan** : **Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.

**New Zealand** : Not determined.

**Philippines** : Not determined.

**Republic of Korea** : Not determined.


**Taiwan** : Not determined.

**Thailand** : Not determined.


**Turkey** : Not determined.

**United States** : Not determined.

**Viet Nam** : Not determined.

**15.2 Chemical Safety Assessment** :  Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

## SECTION 16: Other information

 Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

Q8 T 3000

## SECTION 16: Other information

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification     | Justification      |
|--------------------|--------------------|
| Eye Irrit. 2, H319 | Calculation method |

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

### Full text of abbreviated H statements

|      |   |
|------|---|
| H304 | May be fatal if swallowed and enters airways.           |
| H317 | May cause an allergic skin reaction.                    |
| H318 | Causes serious eye damage.                              |
| H319 | Causes serious eye irritation.                          |
| H411 | Toxic to aquatic life with long lasting effects.        |
| H413 | May cause long lasting harmful effects to aquatic life. |

### Full text of classifications [CLP/GHS]

|                   |   |
|-------------------|---|
| Aquatic Chronic 2 | AQUATIC HAZARD (LONG-TERM) - Category 2         |
| Aquatic Chronic 4 | AQUATIC HAZARD (LONG-TERM) - Category 4         |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                  |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 |
| Skin Sens. 1B     | SKIN SENSITIZATION - Category 1B                |

**Training advice** : Ensure operatives are trained to minimise exposures.

**Date of printing** : 14-10-2022

**Date of issue/ Date of revision** : 14-10-2022

**Date of previous issue** : 29-12-2020

**Version** : 1.01

**Prepared by** : Kuwait Petroleum Research & Technology B.V., The Netherlands

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.