

SAFETY DATA SHEET

Q8 Formula Ultra V 0W-20



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Q8 Formula Ultra V 0W-20
Viscosity or Type : SAE 0W-20

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Lubricating oil for automotive engines

1.3 Details of the supplier of the safety data sheet

Supplier : Q8 Danmark A/S
Arne Jacobsens Allé 7
2300 København S, Danmark
Tel.: +45 7012 4545
Email: produktteknik@Q8.dk
Web: www.Q8.dk

Manufacturer / Distributor : Kuwait Petroleum Belgium N.V./S.A. / Q8Oils Italia S.r.l.
Petroleumkaai 7
B-2020 Antwerp
Belgium
Via Volpedo 2
15050 Castellar Guidobono (AL)
Italy

e-mail address of person responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only.

PCN Information contact : PCNinfo@Q8.com, communication preferably in English only.

1.4 Emergency telephone number

Denmark : +45 8988 2286
Europe : +44 (0) 1235 239 670
Global (English only) : +44 (0) 1865 407 333



National advisory body/Poison Center

Denmark : Bispebjerg Hospital - poison line : +45 8212 1212

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity : None.

Ingredients of unknown ecotoxicity : None.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

SECTION 2: Hazards identification

Precautionary statements

- General** : P103 - Read carefully and follow all instructions.
P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.
- Prevention** : Not applicable.
- Response** : Not applicable.
- Storage** : Not applicable.
- Disposal** : Not applicable.
- Supplemental label elements** : Contains C14-16-18 Alkyl Phenol, Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts and Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1). May produce an allergic reaction. Safety data sheet available on request.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Detergents - Regulation (EC) No 648/2004** : Not applicable.

Special packaging requirements

- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|--|---|-----|---|---|---------|
| Severely refined mineral oil (C15 - C50) - H304 | CAS: * | ≥90 | Asp. Tox. 1, H304 | - | [1] [2] |
| C14-16-18 Alkyl Phenol | REACH #: 01-2119498288-19 EC: 931-468-2 CAS: 1190625-94-5 | ≤3 | Skin Sens. 1B, H317 STOT RE 2, H373 (liver) | Skin Sens. 1, H317: C ≥ 10% | [1] |
| Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts | REACH #: Polymer CAS: 722503-68-6 | <1 | Skin Sens. 1B, H317 Aquatic Chronic 4, H413 | - | [1] |
| Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1) | EC: 601-337-1 CAS: 114959-46-5 | <1 | Skin Sens. 1B, H317 | - | [1] |

Q8 Formula Ultra V OW-20

SECTION 3: Composition/information on ingredients

| | | | | | |
|--|--|--|--|--|--|
| | | | See Section 16 for the full text of the H statements declared above. | | |
|--|--|--|--|--|--|

Contains one or more of the following:

CAS: 64742-56-9, EC: 265-159-2, EU REACH: 01-2119480132-48

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25

CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27

CAS: 64742-70-7, EC: 265-174-4, EU REACH: 01-2119487080-42

CAS: 72623-86-0, EC: 276-737-9, EU REACH: 01-2119474878-16

CAS: 72623-87-1, EC: 276-738-4, EU REACH: 01-2119474889-13

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking

Q8 Formula Ultra V OW-20

SECTION 4: First aid measures

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|---|---|
| Severely refined mineral oil (C15 - C50) - H304 | Working Environment Authority (Denmark, 6/2021). ☐ TWA: 1 mg/m ³ 8 hours. Form: mist and particles EU OEL (Europe). TWA: 5 mg/m ³ 8 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist |

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures

SECTION 8: Exposure controls/personal protection

for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|---|------|----------------------|------------------------|--------------------|----------|
| 14-16-18 Alkyl Phenol Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1) | DNEL | Long term Dermal | 0.3 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 1.17 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Oral | 0.25 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.25 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.5 mg/kg bw/day | Workers | Systemic |

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

| | |
|---|---|
| Physical state | : Liquid. [Oily liquid.] |
| Appearance | : Clear. |
| Color | : Amber. |
| Odor | : Slight |
| Odor threshold | : Not available. |
| Melting point/freezing point | : Not applicable. |
| Pour point | : <input checked="" type="checkbox"/> -42°C (<-43.6°F) [ASTM D 97] |
| Initial boiling point and boiling range | : Not available. |
| Flammability | : Not applicable. |
| Lower and upper explosion limit | : Not available. |
| Flash point | : <input checked="" type="checkbox"/> Open cup: >200°C (>392°F) [ASTM D 92] |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| pH | : Not applicable. |
| Viscosity | : <input checked="" type="checkbox"/> Kinematic (40°C (104°F)): 42.5 mm ² /s (42.5 cSt) [ASTM D 445] Kinematic (100°C (212°F)): 8.6 mm ² /s (8.6 cSt) [ASTM D 445] |
| Solubility(ies) | : |

| Media | Result |
|--|-------------|
| <input checked="" type="checkbox"/> cold water | Not soluble |
| hot water | Not soluble |

Partition coefficient: n-octanol/ water : Not applicable.

| | |
|--------------------------|--|
| Vapor pressure | : <0.01 kPa (<0.075006 mm Hg) |
| Density | : <input checked="" type="checkbox"/> 0.85 g/cm ³ [15.6°C (60.1°F)] [ASTM D 4052] |
| Vapor density | : Not available. |
| Explosive properties | : Not applicable. |
| Oxidizing properties | : Not applicable. |
| Particle characteristics | |
| Median particle size | : Not applicable. |

9.2 Other information

Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

Q8 Formula Ultra V OW-20

SECTION 10: Stability and reactivity

10.5 Incompatible materials : Reactive or incompatible with the following materials:
Strong oxidizing materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|---------------------------------|--------------------|-------------|----------|
| Severely refined mineral oil (C15 - C50) - H304 | LC50 Inhalation Dusts and mists | Rat - Male, Female | 5.53 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1) | LD50 Oral | Rat | >5000 mg/kg | - |

Conclusion/Summary : Not available.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| Severely refined mineral oil (C15 - C50) - H304 | N/A | N/A | N/A | N/A | 5.53 |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---|------------------------------------|---------|-------|----------|-------------|
| Severely refined mineral oil (C15 - C50) - H304 | Eyes - Iris lesion | Rabbit | 0 | 48 hours | 72 hours |
| | Eyes - Redness of the conjunctivae | Rabbit | 0.33 | 48 hours | 72 hours |
| | Skin - Edema | Rabbit | 0 | 72 hours | 7 days |
| | Skin - Erythema/Eschar | Rabbit | 0.17 | 72 hours | 7 days |

Conclusion/Summary : Not available.

Sensitization

| Product/ingredient name | Route of exposure | Species | Result |
|---|-------------------|------------|-----------------|
| Severely refined mineral oil (C15 - C50) - H304 | skin | Guinea pig | Not sensitizing |

Conclusion/Summary : Not available.

Mutagenicity

| Product/ingredient name | Test | Experiment | Result |
|---|---|---|----------|
| Severely refined mineral oil (C15 - C50) - H304 | 474 Mammalian Erythrocyte Micronucleus Test | Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic | Negative |

Conclusion/Summary : Not available.

Carcinogenicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|------------------------|----------------|------|----------|
| Severely refined mineral oil (C15 - C50) - H304 | Negative - Dermal - TC | Mouse - Female | - | 78 weeks |

Conclusion/Summary : Not available.

SECTION 11: Toxicological information

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Development toxin | Species | Dose | Exposure |
|---|-------------------|-----------|-------------------|--------------------|---------------------|----------|
| Severely refined mineral oil (C15 - C50) - H304 | Negative | Negative | Negative | Rat - Male, Female | Oral: 1000 mg/kg | - |

Conclusion/Summary : Not available.

Teratogenicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|-------------------|---------|------------|-----------------|
| Severely refined mineral oil (C15 - C50) - H304 | Negative - Dermal | Rat | 2000 mg/kg | 7 days per week |

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| C14-16-18 Alkyl Phenol | Category 2 | - | liver |

Aspiration hazard

| Product/ingredient name | Result |
|---|--------------------------------|
| Severely refined mineral oil (C15 - C50) - H304 | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
 irritation
 dryness
 cracking
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

SECTION 11: Toxicological information

Potential chronic health effects

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|----------------------------------|--------------------|------------------------|---------------------------|
| Severely refined mineral oil (C15 - C50) - H304 | Sub-acute LOAEL Oral | Rat - Male | 125 mg/kg | 13 weeks; 5 hours per day |
| | Sub-chronic NOAEL Oral | Rat - Male, Female | ≥2000 mg/kg | 13 weeks; 5 days per week |
| | Sub-acute NOAEL Inhalation Vapor | Rat - Male | >980 mg/m ³ | 4 weeks; 5 days per week |

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|-----------------------------------|----------------------------|----------|
| Severely refined mineral oil (C15 - C50) - H304 | Acute NEL >100 mg/l Fresh water | Algae | 72 hours |
| | Acute NEL >10000 mg/l Fresh water | Daphnia - Daphnia Magma | 48 hours |
| | Acute NEL ≥100 mg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Chronic NEL 10 mg/l Fresh water | Daphnia - Daphnia magna | 21 days |

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Severely refined mineral oil (C15 - C50) - H304 | - | - | Inherent |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|-------|-----------|
| Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1) | 5.32 | 23442 | high |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 12: Ecological information

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|---|
| 13 02 05* | mineral-based non-chlorinated engine, gear and lubricating oils |

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Q8 Formula Ultra V OW-20

SECTION 14: Transport information

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Denmark

Product registration number : 4060722

MAL-code : 00-1

Protection based on MAL : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

SECTION 15: Regulatory information

MAL-code: 00-1

Application: When spraying in existing* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During all spraying where atomization occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Full mask with combined filter, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Germany

Hazard class for water (WGK) : 1

Switzerland

VOC content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed, exempted, or notified.

Canada : All components are listed or exempted.

China : Not determined.

Eurasian Economic Union : **Russian Federation inventory:** Not determined.

Japan : **Japan inventory (CSCL):** All components are listed or exempted.
Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.

Philippines : All components are listed or exempted.

Republic of Korea : All components are listed or exempted.

SECTION 15: Regulatory information

| | |
|---------------------------------|--|
| Taiwan | : Not determined. |
| Thailand | : Not determined. |
| Turkey | : Not determined. |
| United States of America | : All components are active or exempted. |
| Viet Nam | : Not determined. |

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

| | |
|-----------------------------------|---|
| Abbreviations and acronyms | : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ASTM = American Society for Testing and Materials ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DIN = German Institute for Standardization DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EC = European Commission EC50 = Half maximal effective concentration EN = European Standard (Norm) EUH statement = CLP-specific Hazard statement GHS - Globally Harmonized System of Classification and Labeling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IC50 = Half maximal inhibitory concentration IMDG = International Maritime Dangerous Goods IMO = International Maritime Organisation ISO = International Organization for Standardization LC50 = Median lethal concentration LD50 = Median lethal dose LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration NOEL / NOEC = No Observed Effect Level / Concentration OECD = Organisation for Economic Co-operation and Development OEL = Occupational Exposure Limit PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006] RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail SDS = Safety Data Sheet SVHC = Substances of Very High Concern STEL = Short Term Exposure Limit TLV = Threshold Limit Value TWA = Time Weighted Average UFI = Unique Formula Identifier UN = United Nations VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative |
|-----------------------------------|---|

Q8 Formula Ultra V OW-20

SECTION 16: Other information

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Not classified.

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

[Full text of abbreviated H statements](#)

| | |
|------|--|
| H304 | May be fatal if swallowed and enters airways. |
| H317 | May cause an allergic skin reaction. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H413 | May cause long lasting harmful effects to aquatic life. |

[Full text of classifications \[CLP/GHS\]](#)

| | |
|-------------------|---|
| Aquatic Chronic 4 | AQUATIC HAZARD (LONG-TERM) - Category 4 |
| Asp. Tox. 1 | ASPIRATION HAZARD - Category 1 |
| Skin Sens. 1B | SKIN SENSITIZATION - Category 1B |
| STOT RE 2 | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |

| | |
|--|--|
| Training advice | : Ensure operatives are trained to minimise exposures. |
| Date of printing | : 21-06-2023 |
| Date of issue/ Date of revision | : 21-06-2023 |
| Date of previous issue | : 16-02-2022 |
| Version | : 1.06 |
| Prepared by | : Kuwait Petroleum Research & Technology B.V., The Netherlands |

[Notice to reader](#)

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.