

# SAFETY DATA SHEET

## Q8 Formula V Blue 0W-20



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : Q8 Formula V Blue 0W-20  
**Viscosity or Type** : SAE 0W-20

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Lubricating oil for automotive engines

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer / Distributor** : Q8 Danmark A/S  
Arne Jacobsens Allé 7  
2300 København S,  
Danmark  
Tel. 7012 4545, Fax 4599 2020  
Email: produktteknik@Q8.dk, Web: www.Q8.dk

**e-mail address of person responsible for this SDS** : SDSinfo@Q8.com, communication preferably in English only.

#### 1.4 Emergency telephone number

**Denmark** : +45 8988 2286  
**Europe** : +44 (0) 1235 239 670  
**Global (English only)** : +44 (0) 1865 407 333



### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

**Ingredients of unknown toxicity** : None.

**Ingredients of unknown ecotoxicity** : None.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Signal word** : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

#### Precautionary statements

**General** : P103 - Read label before use.  
P102 - Keep out of reach of children.  
P101 - If medical advice is needed, have product container or label at hand.

**Prevention** : Not applicable.

**Response** : Not applicable.

Q8 Formula V Blue 0W-20

## SECTION 2: Hazards identification

- Storage** : Not applicable.
- Disposal** : Not applicable.
- Supplemental label elements** : Contains C14-16-18 Alkyl Phenol, Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1) and Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt. May produce an allergic reaction. Safety data sheet available on request.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type	Notes
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥50 - ≤75	Asp. Tox. 1, H304	[1] [2]	L
Mineral oil	CAS: *	≤10	Not classified.	[2]	-
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	REACH #: 01-2119486452-34 EC: 500-183-1 CAS: 68037-01-4	≤10	Asp. Tox. 1, H304	[1]	-
bis(nonylphenyl)amine	REACH #: 01-2119488911-28 EC: 253-249-4 CAS: 36878-20-3	≤3	Aquatic Chronic 4, H413	[1]	-
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	REACH #: 01-0000015551-76, 01-2119878226-29, 01-2119830067-43 EC: 406-040-9 CAS: 125643-61-0 Index: 607-530-00-7	≤3	Aquatic Chronic 4, H413	[1]	-
C14-16-18 Alkyl Phenol	REACH #: 01-2119498288-19	≤3	Skin Sens. 1B, H317 STOT RE 2, H373 (liver)	[1]	-

Q8 Formula V Blue 0W-20

## SECTION 3: Composition/information on ingredients

			<b>See Section 16 for the full text of the H statements declared above.</b>		
--	--	--	---	--	--

\* CAS: 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-62-7, 64742-65-0, 64742-71-8, 72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
  - irritation
  - dryness
  - cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, alcohol-resistant foam or water spray (fog).

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
sulfur oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Distillates (petroleum), hydrotreated heavy paraffinic Mineral oil	<b>Working Environment Authority (Denmark, 5/2020).</b> TWA: 1 mg/m <sup>3</sup> 8 hours. Form: mist and particles <b>Working Environment Authority (Denmark, 10/2012).</b> TWA: 1 mg/m <sup>3</sup> 8 hours. Form: mist and particles

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Exposure	Value	Population	Effects
bis(nonylphenyl)amine  reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	DNEL	Long term Oral	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	0.16 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.22 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.33 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.74 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	2.33 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Dermal	20 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	875 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	1750 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	0.006 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Short term Dermal	1 mg/cm <sup>2</sup>	Workers	Local
DNEL	Short term Dermal	8.33 mg/cm <sup>2</sup>	General population	Local	

### PNECs

No PNECs available.

### 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## SECTION 8: Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Appearance** : Clear.
- Color** : Green. [Dark]
- Odor** : Slight
- Odor threshold** : Not available.
- pH** : 8
- Melting point/freezing point** : -54°C
- Initial boiling point and boiling range** : >300°C
- Flash point** : Open cup: 220°C [ASTM D92.]
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not applicable.
- Upper/lower flammability or explosive limits** : Not available.
- Vapor pressure** : <0.01 kPa
- Vapor density** : Not available.
- Density** : 0.85 g/cm<sup>3</sup> [15°C]
- Solubility(ies)** : Insoluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Auto-ignition temperature** : >300°C
- Decomposition temperature** : >300°C
- Viscosity (40°C)** : 43.9 cSt
- Viscosity (100°C)** : 8.3 cSt
- Explosive properties** : Not applicable.
- Oxidizing properties** : Not applicable.

### 9.2 Other information

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
Strong oxidizing materials
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Mineral oil	LC50 Inhalation Dusts and mists	Rat - Male, Female	5.53 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

**Conclusion/Summary** : Not toxic.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Mineral oil	N/A	N/A	N/A	N/A	5.53

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Mineral oil	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
	Skin - Edema	Rabbit	0	72 hours	7 days
	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours

#### **Conclusion/Summary**

- Skin** : Non-irritant to skin.
- Eyes** : Non-irritating to the eyes.
- Respiratory** : Non-irritant to lungs.

#### Sensitization

Product/ingredient name	Route of exposure	Species	Result
Mineral oil	skin	Guinea pig	Not sensitizing

#### **Conclusion/Summary**

- Skin** : Not sensitizing
- Respiratory** : Not classified for respiratory sensitization.

#### Mutagenicity



## SECTION 11: Toxicological information

Product/ingredient name	Test	Experiment	Result
Mineral oil	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

**Conclusion/Summary** : No known significant effects or critical hazards.

### Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Mineral oil	Negative - Dermal - TC	Mouse - Female	-	78 weeks

**Conclusion/Summary** : No carcinogenic effect.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Mineral oil	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/kg	-

**Conclusion/Summary** : No known significant effects or critical hazards.

### Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Mineral oil	Negative - Dermal	Rat	2000 mg/kg	7 days per week

**Conclusion/Summary** : No known significant effects or critical hazards.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
C14-16-18 Alkyl Phenol	Category 2	-	liver

### Aspiration hazard

Product/ingredient name	Result
Distillates (petroleum), hydrotreated heavy paraffinic Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : Defatting to the skin. May cause skin dryness and irritation.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : Adverse symptoms may include the following:  
 irritation  
 dryness  
 cracking

## SECTION 11: Toxicological information

**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Mineral oil	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week
	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m <sup>3</sup>	4 weeks; 5 days per week

**Conclusion/Summary** : Not toxic.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Mineral oil	Acute NEL >100 mg/l Fresh water	Algae	72 hours
	Acute NEL >10000 mg/l Fresh water	Daphnia - Daphnia Magma	48 hours
	Acute NEL ≥100 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia magna	21 days

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Mineral oil	-	-	Inherent

### 12.3 Bioaccumulative potential

## SECTION 12: Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated bis(nonylphenyl)amine	>6.5	-	high
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate	3.64 to 7.02 9.2	1730 260	high low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### European waste catalogue (EWC)

Waste code	Waste designation
13 02 06*	synthetic engine, gear and lubricating oils

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

Q8 Formula V Blue 0W-20

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorization

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

##### Other EU regulations

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

##### Ozone depleting substances (1005/2009/EU)

Not listed.

##### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

##### Seveso Directive

## SECTION 15: Regulatory information

This product is not controlled under the Seveso Directive.

### National regulations

**Product registration number** : 4221717

**MAL-code** : 00-1

**Protection based on MAL** : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 00-1

**Application:** When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During all spraying where atomization occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Full mask with combined filter, coveralls and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

**Hazard class for water (WGK)** : 1

**VOC content** : Exempt.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

## SECTION 15: Regulatory information

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

<b>Australia</b>	: All components are listed or exempted.
<b>Canada</b>	: All components are listed or exempted.
<b>China</b>	: All components are listed or exempted.
<b>Europe</b>	: All components are listed or exempted.
<b>Japan</b>	: <b>Japan inventory (CSCL)</b> : All components are listed or exempted. <b>Japan inventory (ISHL)</b> : Not determined.
<b>New Zealand</b>	: All components are listed or exempted.
<b>Philippines</b>	: All components are listed or exempted.
<b>Republic of Korea</b>	: All components are listed or exempted.
<b>Taiwan</b>	: All components are listed or exempted.
<b>Thailand</b>	: Not determined.
<b>Turkey</b>	: Not determined.
<b>United States</b>	: Not determined.
<b>Viet Nam</b>	: Not determined.

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

### Full text of abbreviated H statements

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.

### Full text of classifications [CLP/GHS]

Aquatic Chronic 4	AQUATIC HAZARD (LONG-TERM) - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

**Training advice** : Ensure operatives are trained to minimise exposures.

**Date of printing** : 15-02-2021

Q8 Formula V Blue 0W-20

## SECTION 16: Other information

**Date of issue/ Date of revision** : 15-02-2021  
**Date of previous issue** : 27-01-2020  
**Version** : 1.06  
**Prepared by** : Kuwait Petroleum Research & Technology B.V., The Netherlands

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.